

Technical Data Sheet 304

BaseColor Matt

1 Product Description

BaseColor Matt is a water-based primer/undercoat with excellent adhesion and opacity and forms an integral part of the Perlata and Escenta decorative coating systems. Apply BaseColor Matt to surfaces which are prepared ready for painting. BaseColor Matt can be tinted to a wide range of colours.

2 Properties

- Water-based low odour product.
- Excellent adhesion and opacity.
- 39.0% volume solids.
- 1.50g/ml density.
- Touch dry in 2 hrs (at 20°C).
- Overcoating time 4 – 8 hrs.
- Coverage rate: approximately 10 - 14 m²/lt/coat.
One 2.5 lt unit will cover approximately 30 m² (300 ft²).

3 Limitations

For interior use only.

4 Preparation

4.1 New Surfaces

- Ensure all surfaces are sound, clean and suitably dry.
- Dense or highly polished surfaces should be coated with an appropriate primer to promote effective adhesion.
- Porous surfaces should be primed with a mist coat of BaseColor Matt thinned with up to 20% clean water.
- Leave to dry.

4.2 Previously decorated surfaces

- Ensure all surfaces are sound, clean and suitably dry.
- Remove any loose or flaking material back to a sound firm edge.
- Treat any organic growth with a fungicidal wash.
- Fill any holes, cracks or surface defects.
- Surfaces that exhibit high sheen levels should be wet abraded to provide a key.

- Wash down sound paintwork with warm water and an appropriate cleaning agent to remove any contaminants.
- Rinse surfaces with clean water to remove any residues.
- Spot prime any bare or filled areas with a mist coat of BaseColor Matt or an appropriate primer as necessary.
- Leave to dry.

5 Application Instructions

Stir product thoroughly before use.
Brush/roller or conventional/airless spray.

6 Health and Safety

BaseColor Matt is a non-toxic, water-based product. Ensure good ventilation during application and drying. Avoid contact with skin and eyes. Keep out of reach of children.

Please refer to Material Safety Data Sheet for further information.

7 Storage

Store in good dry conditions between 5 – 25°C. Protect from frost. Protect from sunlight and sources of direct heat. Keep container sealed when not in use.

Shelf life of BaseColor Matt in an unopened container under correct storage condition is 12 months from date of manufacture.

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.

SAT TDS304 0107©

Armourcoat Limited
Morewood Close London Road
Sevenoaks Kent TN13 2HU United Kingdom
Tel: +44 (0)1732 460 668 Fax +44 (0)1732 450 930
Email: technical@armourcoat.co.uk
web: www.armourcolor.com